


# CHRYSO® RocaSol M

Surface hardener

Water repeller



**CHRYSO® RocaSol M** is a water-based liquid sealer that penetrates concrete and reacts with the available lime in concrete.

Thanks to the reaction between the inorganic compounds and lime in the pores of concrete, concrete abrasion resistance is increased and permeability reduced without any change in the surface aspect and shade.

Thanks to its action, **CHRYSO® RocaSol M** strengthens mechanically substrate made of hydraulic binders and slows down the alkali process of concrete.

## Indicative characteristics

- Nature: liquid
- Colour: Colourless
- Specific gravity: 1,030 ± 0,010
- pH: 13,00
- Shelf life: 12 months

## Domains of application

- Exposed aggregate concrete
- Decorative concrete
- Precast elements
- Slabs in natural stone (limestone)
- Street furniture

## Precautions

Stir before use

Protect from frost.

Apply **CHRYSO® RocaSol M** on clean, dust-free and dry surfaces. Puddles area are swept away with a wet rag.

Do not apply the product at temperatures below 5 °C or above 30 °C and in case on hot surfaces.

Do not apply when it is raining or on high temperatures.

## Method of use

Consumption: Dosage rate: 150 to 200 g/m<sup>2</sup>.

**CHRYSO® RocaSol M** dosage rate depends on the surface porosity. The average is for one coat 1 litre for 5 m<sup>2</sup>.

## Surface preparation

Surfaces must be clean, sound, and free of dust, dirt and contamination. If necessary, sweep all areas to be treated with a fine bristle broom, hose off with water and let dry.

## Application

Before application, surfaces must be wet.

**CHRYSO® RocaSol M** is ready-to-use and is applied in two coats or more with spraying equipment. Spray fresh on fresh in crossed coats until saturation of the surface.

Spraying equipment will be cleaned with water, immediately after use.

## Safety

Before use, refer to the Material Safety Data Sheet.

The MSDS is available on [www.chryso.com](http://www.chryso.com)



The information contained in this technical data sheet is given to the best of our knowledge and the result from extensive testing - which were conducted in order to remain as objective as possible. However, it cannot, in any case, be considered as a warranty involving our liability in case of misuse or any different use of our products, other than those from the «Application» paragraph of this technical data sheet. Some application tests should be carried out before using the product to ensure that the methods of use and conditions of application of the product are satisfactory. Our technical assistance is at the disposal of the users. Please enquire for the most recent version of the technical data sheet, available on [www.chryso.com](http://www.chryso.com).

CHRYSO S.A.S. - 19 Place de la Résistance - 92446 Issy-les-Moulineaux cedex - FRANCE - Tel.: +33 (0)1 41 17 18 19 - Fax: +33 (0)1 41 17 18 80

