



CHRYSO® Dem Elio P50 - DPS

Delayed mould release agent

Pure synthesis

CHRYSO® Dem Elio P50 - DPS is a delayed mould release agent which, when sprayed onto the surface of a metallic, plastic or wooden mould ensures easy mould release on all concretes after the cement has hardened.

While improving the visual appearance of the concrete facing, **CHRYSO® Dem Elio P50 - DPS** will allow the subsequent application of rendering and paint according to the conditions defined by the professional practice rules for the application of coatings.

Indicative characteristics

- Nature: liquid
- Colour: Yellow
- Shelf life: 24 months

Specifications

- Specific gravity: < 1,000
- Cinematic viscosity: 25,0 mm²/s (cSt) ± 5,0 mm²/s (cSt)

Norms and regulations

- Conforms for PCB content with legislation in force (Directives of the European Communities Council No. 85/467/CEE of 1st October 85 – OJ of the European Communities L269 of 11 October 1985).

Domains of application

- Poured concrete
- Precast
- Any concrete delayed mould-release, including strongly steam-cured ones

Precautions

For special support or applications with white cement, it is advisable to run a compatibility test before any particular use.

In the case of freezing and lumping, defrost and mix again before use.

Method of use

Consumption: metallic or plastic mould: 50 m²/l
wooden formwork: 30 m²/l

This product must be applied by spraying (all types of equipment), in a regular film, without any gaps or overload. Any excess would render mould-releasing difficult.

Safety

Before use, refer to the Material Safety Data Sheet.

The MSDS is available on www.chryso.com