

CHRYSO®Premia 205

High range water reducing Super plasticizing admixture



CHRYSO®Premia 205 is a new generation superplasticizer high range water reducer, based on modified polycarboxylate.

CHRYSO®Premia 205 is particularly recommended for concrete requiring high short and long-term compressive strengths.

CHRYSO®Premia 205 enables very low W/C ratios to be produced in the concrete.

CHRYSO®Premia 205 is particularly recommended for self-levelling concrete.

Thanks to its short-term performances, **CHRYSO®Premia 205** allows whether to reduce the time before demoulding or to save energy by decreasing temperature or time of steam curing.

Indicative characteristics

- Nature: liquid
- Colour: Opalescent green-grey
- Shelf life: 9 months

Specifications

- Specific gravity At 20°C: $1,055 \pm 0,010$
- pH: $5,00 \pm 1,00$
- Solid content (halogen): $30,30\% \pm 1,50\%$
- Solid content (EN 480-8): $30,30\% \pm 1,50\%$
- Na₂O equivalent: $\leq 1,00\%$
- Cl⁻ ions content: $\leq 0,01\%$

Norms and regulations

- This product conforms to CE marking. The appropriate declaration can be found on our internet site.
- This product conforms to NF 085 certification, which technical specifications are those applied in the non harmonised part of NF EN 934-2.

Domains of application

- All cement types
- Self consolidating concrete
- Slump flow superior to 50 mm
- Steam-cured concrete
- High performance Concrete - Very High Performance Concrete - Ultra High Performance Concrete
- Prestressed concrete
- Precast

Precautions

Protect from frost.

Avoid prolonged exposure to high temperatures. Should the product freeze, it will recover its properties. After thawing, an efficient agitation is necessary until the product is entirely homogeneous again.

Method of use

Dosage: 0.3 to 3.0 kg per 100 kg of cement

A 0.8% dosage of the product of the weight of cement is commonly used.

This product must be added to the mixing water or later on, on concrete.

Safety

This product is classified as "harmless". In case of exposure, it is recommended to wear your protective equipment.

Before use, refer to the safety data sheet on our internet site www.chryso.com



The information contained in this technical data sheet is given to the best of our knowledge and the results from extensive testing in order to remain as objective as possible. However, it cannot, in any case be considered as a warranty involving our liability in case of misuse or any different use of our products from the "Application" paragraph of this technical data sheet. Some application tests should be carried out before using the product to ensure that the methods of use and conditions of application of the product are satisfactory. Our technical assistance is at the disposal of the users.

Please enquire for the most recent version of the technical datasheet, available on www.chryso.com

CHRYSO S.A.S. - 19 Place de la Résistance - 92446 Issy les Moulinaux cedex - France - Tel : +33 (0)1 41 17 18 19 - Fax : +33 (0)1 41 17 18 80