


CHRYSO® FiniSol Mat

Concrete Sealer

Matt finish



CHRYSO® FiniSol Mat is a water-based concrete sealer designed to protect aesthetic concretes.

CHRYSO® FiniSol Mat is a film-forming sealer that reduces stains and protects against oils and dust.

CHRYSO® FiniSol Mat does not modify the aspect and the colour of the substrate on which it is applied.

Indicative characteristics

- Nature: liquid
- Colour: Milky white
- Specific gravity (20 °C): $1,070 \pm 0,020$
- pH: $11,00 \pm 1,00$
- Freezing point: -2 °C
- Shelf life: 18 months

Domains of application

- Cellars
- Garage
- Parking areas
- Industrial floors
- Terraces,
- Exposed aggregate concrete
- All concrete, mortar, fibrocement materials
- Facing panels

Precautions

Protect from frost.

CHRYSO® FiniSol Mat must be applied onto clean, dust-free and grease-free surfaces, without any crumbly particles.

CHRYSO® FiniSol Mat should not be applied onto bituminous materials.

It is necessary to avoid excessive application of

CHRYSO® FiniSol Mat onto a non-porous material. In this particular case, diluting the product is essential in order to avoid surface

bleaching.

Method of use

Consumption: 5 to 10 m² per litre.

CHRYSO® FiniSol Mat is a ready to use product and can be applied with a roller or spraying equipment, both for indoor and outdoor projects.

When necessary, this product can be diluted with water (10 to 20%) to enable it to penetrate more easily.

In order to protect the concrete, the product must be applied onto hardened concrete (minimum 7 days old). When the condition of the material requires a second application, the latter can be applied 30 minutes after the first one, provided the ambient temperature is at least 10 °C.

Safety

Before use, refer to the Material Safety Data Sheet.



The information contained in this technical data sheet is given to the best of our knowledge and the result from extensive testing - which were conducted in order to remain as objective as possible. However, it cannot, in any case, be considered as a warranty involving our liability in case of misuse or any different use of our products, other than those from the «Application» paragraph of this technical data sheet. Some application tests should be carried out before using the product to ensure that the methods of use and conditions of application of the product are satisfactory. Our technical assistance is at the disposal of the users. Please enquire for the most recent version of the technical data sheet, available on www.chryso.com.

CHRYSO S.A.S. - 19 Place de la Résistance - 92446 Issy-les-Moulineaux cedex - FRANCE - Tel.: +33 (0)1 41 17 18 19 - Fax: +33 (0)1 41 17 18 80

