


CHRYSO® Revello Color

Tinted waterproofing liquid hardener for precast concrete



CHRYSO® Revello Color is a tone on tone ready-to-use tinted hardener (non film-forming) for the strengthening, the waterproofing and the enhancement of all mineral porous substrate made of cement.

CHRYSO® Revello Color chemically reacts with the free lime and forms an insoluble silicate mineral into the capillaries. Thanks to this reaction, **CHRYSO® Revello Color** waterproofs the surface and renders it highly resistant to chemical attacks (de-icing salts, cleaning products, high pressure cleaning, climatic aggressions...).

CHRYSO® Revello Color gives to concrete a harder surface, stops the dusting phenomena and neutralizes the alkali process of concrete, thus reducing efflorescence.

Thanks to its tailor-made matching coloring, **CHRYSO® Revello Color** homogenizes the treated surfaces while not modifying their mineral aspect.

Indicative characteristics

- Nature: liquid
- Colour: Tailor-made according to the requested colour
- Specific gravity: 1,050
- Shelf life: 12 months

Domains of application

- Facing blocks
- Kerbs
- Fence elements (panels, posts - drycast)
- Paving blocks

Precautions

Stir before use
Protect from frost.

Product application must be done on clean and dust-free substrate. It must not have been coated with other organic synthetic film-forming product (such as paints, resins, film-forming sealers...)

Apply in dry and non windy conditions on substrates with temperatures between 5 and 30 °C.

Method of use

Consumption: 100 to 200 g/m² with a specific spraying system for an homogeneous application (e.g.: AIRMIX HVLP or Airless): application in one to two coats. The second coat is to be applied once initial coat has gone tacky. Avoid over dosage.

The consumption of this product depends on the porosity of surface.

Surface preparation


Product application must be done on clean, dust-free, grease-free and dry substrate, free from residues. It must not have been coated earlier with other organic synthetic film-forming products (paints, resins, waterproofers and various film-forming coating). In this case, remove them using the products of CHRYSO® CleanSol range to clean urban and vegetable dirt.

Application

Before application protect absolutely all substrates around the jobsite (glass, paints, woodwork, door frame...). Always carry out a trial

CHRYSO® Revello Color

Tinted waterproofing liquid hardener for precast concrete



before treatment.

CHRYSO® Revello Color is ready-to-use and can be applied with a foam roller or a HVLP sprayer, for indoor or outdoor purpose.

CHRYSO® Revello Color can be applied on seemingly dry substrates.

Color is dry to the touch from 30 minutes after application, depending on weather conditions.

The mineralizing process will happen progressively during several weeks.

Clean all equipment with water.

Safety

Before use, refer to the Material Safety Data Sheet.

The MSDS is available on www.chryso.com



The information contained in this technical data sheet is given to the best of our knowledge and the result from extensive testing - which were conducted in order to remain as objective as possible. However, it cannot, in any case, be considered as a warranty involving our liability in case of misuse or any different use of our products, other than those from the «Application» paragraph of this technical data sheet. Some application tests should be carried out before using the product to ensure that the methods of use and conditions of application of the product are satisfactory. Our technical assistance is at the disposal of the users. Please enquire for the most recent version of the technical data sheet, available on www.chryso.com.

CHRYSO S.A.S. - 19 Place de la Résistance - 92446 Issy-les-Moulineaux cedex - FRANCE - Tel.: +33 (0)1 41 17 18 19 - Fax: +33 (0)1 41 17 18 80

