



# CHRYSO® Dem XTra 200

## Delayed mould release agent

### Pure synthesis

CHRYSO® Dem Xtra 200 is a ready-to-use delayed mould-release agent which does not contain any solvent.

CHRYSO® Dem Xtra 200 forms a non-adhering film on the surface of the formwork that withstands very high temperatures. Concrete can be easily separated after setting without affecting the facing.

CHRYSO® Dem Xtra 200 produces attractive surface finishes without any bubbling or staining, ready to be covered with subsequent coatings. It has no detrimental action with respect to most rubbers, plastics and polystyrenes.

While improving the appearance of concrete facing, CHRYSO® Dem Xtra 200 allows the subsequent application of coating and paint according to the conditions defined by the professional practice rules for the application of coatings.

### Indicative characteristics

- Colour: Yellow
- Specific gravity: < 1,000
- Cinematic viscosity (20°C): 42,0 mm<sup>2</sup>/s (cSt) ± 6,0 mm<sup>2</sup>/s (cSt)

### Specifications

- Nature: liquid
- Shelf life: 24 months

### Domains of application

- All cement types
- Steam-cured concrete
- Poured concrete
- Metallic formworks

- Plastic formworks
- All kinds of delayed mould-release elements

### Precautions

For special support (synthetic or PU type) or applications with white cement, it is advisable to run a compatibility test before any particular use. Should the product freeze, it will recover its properties. After thawing, an efficient agitation is necessary until the product is entirely homogeneous again.

### Method of use

The consumption of this product depends on the type of support and the application process.

This product must be applied by spraying, with a roll or a paint brush, in a regular film, without any gaps or overload.

To eliminate any excess oil, after spraying, we recommend running over with a scraper.

The quality of the application has a direct influence on the aspect finish.

### Safety

Before use, refer to the Material Safety Data Sheet.

The MSDS is available on [www.chryso.com](http://www.chryso.com)



The information contained in this technical data sheet is given to the best of our knowledge and the result from extensive testing - which were conducted in order to remain as objective as possible. However, it cannot, in any case, be considered as a warranty involving our liability in case of misuse or any different use of our products, other than those from the «Application» paragraph of this technical data sheet. Some application tests should be carried out before using the product to ensure that the methods of use and conditions of application of the product are satisfactory. Our technical assistance is at the disposal of the users. Please enquire for the most recent version of the technical data sheet, available on [www.chryso.com](http://www.chryso.com).

CHRYSO S.A.S. - 19 Place de la Résistance - 92446 Issy-les-Moulineaux cedex - FRANCE - Tel.: +33 (0)1 41 17 18 19 - Fax: +33 (0)1 41 17 18 80

