


CHRYSO® FiniSafe

Concrete finishing aid solution



CHRYSO®FiniSafe is developed to help in the implementation of indoor and outdoor concrete. Applied on the surface, CHRYSO®FiniSafe facilitates mechanical or manual float operations while improving the workability of the concrete surface for final floating.

CHRYSO®FiniSafe greatly facilitates the floating phase and thus makes it faster, less painful for operators and gives a smoother and more consistent finish.

Benefits

- Provides a smoother finish and creates better surface consolidation.
- Reduces operator efforts and optimizes his production time.
- Avoid the addition of water during the float, detrimental to concrete's performance.
- Applying the CHRYSO®FiniSafe just before the mechanical trowel passes improves machine performance while reducing wear.
- Concrete can then receive other surface treatments without specific preparation.
- Does not change neither color nor appearance of the support.

Fields of application

Precast

- Precast concrete elements intended to be floated

Ready Mix

- All types of concrete floors:
 - Standard concrete
 - Industrial flooring
 - Decorative concrete: colored, printed, polished, brushed, exposed aggregates...etc.

Application

- Use a sprayer to apply the product, e.g.:
 - CHRYSO®Pulvo M5 or equivalent sprayer
 - Hand sprayer (ref. 1002)
 - Industrial Pump Sprayer (ref. 222180XP)
- Spreading rate: 10 to 20 m² / L
- Application on first day of casting
- Several applications are possible
- Clean tools with water
- Thoroughly clean the sprayer after use

Properties

- Nature: liquid
- Water-based
- Ready-to-use
- Packaging: 5 L, 20 L, 215 L, 1000 L
- Shelf life: 12 months

Precautions

- Before use, protect the surroundings areas to prevent contact with the product.
- Before floating or troweling, test CHRYSO®FiniSafe on a sample section to determine appropriate application rate before applying to entire area.
- The container must be stored, sealed and protected from frost, between 5 ° C and 45 ° C. In case of frost, do not use the product.
- It is necessary to float the concrete after CHRYSO®FiniSafe application. Otherwise, it may leave a whitish film after drying.

Safety

- Before use, read carefully the safety data sheet available on our website www.chryso.com or from your local CHRYSO representative.



Les informations contenues dans la présente fiche technique sont l'expression de nos connaissances et de résultats d'essais effectués dans un souci constant d'objectivité. Elles ne peuvent cependant, en aucun cas, être considérées comme apportant une garantie ni comme engageant notre responsabilité en cas d'application défectueuse ou d'utilisation de nos produits en dehors des stipulations du paragraphe « Application » de la fiche technique. Des essais préalables à chaque utilisation devront être effectués par les utilisateurs et permettront ainsi de vérifier que les modes d'emploi et les conditions d'application donnent satisfaction. Notre assistance technique se tient à la disposition des utilisateurs. Consulter la version la plus récente de la fiche technique, disponible sur www.chryso.com

CHRYSO S.A.S. – 19 Place de la Résistance – 92446 Issy-les-Moulineaux cedex – France – Tel : +33 (0)1 41 17 18 19 – Fax : +33 (0)1 41 17 18 80