TECHNICAL DATA SHEET







CHRYSO® Plast RMD

Water reducing Plasticizing admixture

DESCRIPTION

CHRYSO® Plast RMD is a water reducing plasticiser, which allows an increase dispersion of the cement particles in concrete. CHRYSO® Plast RMD optimises the dosage of cement required to obtain a given compressive strength.

For an equivalent consistence with reduced water content:

- Increased compressive strength.
- Improved mix cohesion, allowing sand content optimisation, or increased use of harsh or gap graded materials.
- Reduced capillary action resulting in less permeable concrete.

BENEFITS

- Improved compaction.
- Increased concrete strengths.
- Reduced mould wear.
- Improved production rates.
- · Cement optimisation without strength loss.
- Wide range of applications.
- Versatile dosage range.

FIELDS OF APPLICATION

Types of Application

- All types of cement
- Ready-mix concrete
- Reinforced precast concrete
- Heavy precast elements
- Prestressed concrete
- Pumped concrete

INDICATIVE INFORMATION

Product Nature	liquid
Color	Brown
Lifetime	12 months
Cl⁻ lons content	≤ 0,100 %
Equivalent Content NA ₂ O	≤ 1,00 %
Specific gravity	1,185 ± 0,010

PACKAGING

- IBC 1000L
- Bulk delivery on request

METHOD OF USE

Dosage:

0.2 to 0.8 kg for 100 kg of cement.

A 0.3% dosage of the product to weight of cement is commonly used.

The optimum dosage of CHRYSO® Plast RMD can only be established after trial tests, taking into account local conditions affecting the workability of the mix and the mechanical properties required from the concrete.

CHRYSO® Plast RMD is completely miscible in water and must be added to the mixing water.

PRECAUTIONS

- Increased dosage may result in increased air content and set retardation
- Store away from frost.
- Should the product freeze, it will recover its properties after thawing and agitating.

NORMATIVE AND REGULATORY INFORMATION

CHRYSO® Plast RMD is a plasticiser – water reducer which conforms to UKCA and CE marking.

SAFETY

This product is classified as "harmless". In case of exposure, it is recommended to wear your normal protective equipment.

The information contained in this document is given to the best of our knowledge and is the result of extensive and controlle d t esting. However, it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be con ducted before the product is used to ensure that the methods and conditions of use of the product are satisfactory. Our specialists remain at the disposal of customers if they require help with the application of the product for their specific needs. www.chryso.uk

CHRYSO UK Ltd. - 9 Brunel Close, Drayton Fields Industrial Estate. NN11 8RB. Daventry, United Kingdom Tél.:+44 (0) 132770797 Fax:+44 (0) 13277079



TECHNICAL DATA SHEET







CHRYSO® Plast RMD

Water reducing Plasticizing admixture

For further information, please refer to the safety data sheet on our internet site www.uk.chryso.com.

The information contained in this document is given to the best of our knowledge and is the result of extensive and controlle d t esting. However, it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be con ducted before the product is used to ensure that the methods and conditions of use of the product are satisfactory. Our specialists remain at the disposal of customers if they require help with the application of the product for their specific needs. www.chryso.uk

CHRYSO UK Ltd. - 9 Brunel Close, Drayton Fields Industrial Estate. NN11 8RB. Daventry, United Kingdom Tél.:+44 (0) 132770797 Fax:+44



