

Chryso® Optima 100

Water reducing Plasticizing admixture

DESCRIPTION

CHRYSO® Optima 100 is a plasticiser – water reducer which works as a new generation superplasticiser based on modified phosphonate. Its specifically designed molecular structure gives it exceptional properties as a concrete additive.

Using **CHRYSO® Optima 100** results extensive workability at all levels of consistency, compared to standard additives. In this respect, **CHRYSO® Optima 100** is particularly adapted to the pumping of concrete over long distances.

CHRYSO® Optima 100 is compatible with most types of cement / admixture incompatibility. On account of all these characteristics.

CHRYSO® Optima 100 is a superplasticiser which is particularly adapted for use on construction sites and in the ready mix concrete industry.

FIELDS OF APPLICATION

Types of Application

- All types of cement
- Hot weather concreting
- Pumped concrete
- Extended workability retention
- Concrete for highly reinforced structures
- High performance concrete – very high performance concrete
- Prestressed concrete

INDICATIVE INFORMATION

Product Nature	Liquid
Color	Cream
Lifetime	9 months
Halogen Dry Extract	30,00 % ± 1,50
Cl⁻ Ions content	≤ 0,100 %
Equivalent Content Na₂O	≤ 0,30 %
Specific gravity	1,060 ± 0,010
pH	3,20 ± 1,00
Freezing Point	-3 °C

PACKAGING

- Container of 1000L
- Bulk delivery on request

METHOD OF USE

Dosage :

0.3 to 5.0 kg for 100 kg of cement.

- A 1.0% dosage of the product of the weight of cement is commonly used.
- This product is completely miscible in water.
- This product must be added to the mixer with the mixing water.
- The product can also be added later on site.
- The optimum dosage of this product can only be established after trial tests, taking into account the rheological characteristics and the required mechanical performances of the concrete.
- Dependant on application this product can be used in conjunction with some other CHRYSO® admixtures.

PRECAUTIONS

- Protect from frost.
- Should the product freeze, it will recover its properties. After thawing, an efficient agitation is necessary until the product is entirely homogeneous again.
- Avoid prolonged exposure to high temperatures

NORMATIVE AND REGULATORY INFORMATION

- This product conforms to UKCA and CE marking. The appropriate declaration can be found on our internet site

SAFETY

CHRYSO® Optima 105 is a product classified as "harmless". It is recommended to wear normal protective equipment.

For further information, please refer to the safety data sheet on our internet site www.uk.chryso.com.

TECHNICAL DATA SHEET

Chryso® Optima 100

Water reducing Plasticizing admixture

UK
DK



Chryso
Concrete
Solutions

24/06/2026

The information contained in this document is given to the best of our knowledge and is the result of extensive and controlled testing. However, it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be conducted before the product is used to ensure that the methods and conditions of use of the product are satisfactory. Our specialists remain at the disposal of customers if they require help with the application of the product for their specific needs.

CHRYSO UK Ltd. - 1 Herald Way, Binley Industrial Estate, Coventry, United Kingdom, CV3

P.2/2