

## Chryso® Cure HPE

Curing Agent  
Water based

Chryso  
Concrete  
Solutions

24/06/2026

### DESCRIPTION

Chryso® Cure HPE is a **ready-to-use, water-based curing agent** designed for freshly placed concrete, mortars, cement-based coatings, and newly demoulded concrete. It forms a continuous protective film that prevents moisture loss (desiccation), promoting more complete cement hydration. This reduces **early-age cracking** and **drying shrinkage**, while improving **abrasion resistance** after the concrete sets.

The product is **white on application** for clear visual control and becomes **colourless once fully dry**.

### FIELDS OF APPLICATION

Chryso® Cure HPE is especially suited to concrete elements requiring controlled curing and moisture retention, including:

- High surface-area concrete components such as **slabs, roads, and highways**
- Precast walling**
- Any cement-based element at risk of **excessive desiccation**
- Concrete and mortar exposed to adverse drying conditions, including:
  - High ambient temperatures**
  - Wind exposure**

### INDICATIVE INFORMATION

|                               |                 |
|-------------------------------|-----------------|
| Product Nature                | Liquid          |
| Color                         | White           |
| Lifetime                      | 9 months        |
| Specific gravity              | 0,975 ± 0,020   |
| Dry Extract (SYNAD - IFSTTAR) | 29,50 % ± 1,40  |
| Afnor Cut Viscosity           | 30,00 s ± 10,00 |

### PACKAGING

- 5L Container
- 20L Container
- 215 L Barrel

### METHOD OF USE

**Dosage :**

- Standard dosage: **100–200 g/m²**
- Reference dosage: **200 g/m²**
- Product is **ready-to-use** with no dilution required

**Application for effective curing performance:**

- Apply **preferably on fresh concrete** to prevent desiccation.
- Spray an even, uniform film at **100–200 g/m²**, adjusting for surface roughness.
- Use **two crossed passes** to avoid untreated areas.
- For trowel finishing assistance:
  - Apply **30–50 g/m²** before finishing
  - After finishing, apply an additional coat if needed
- Rinse spray equipment with **clean water** before the product dries

### PRECAUTIONS

- Homogenise before use.
- Treated surfaces can become slippery when wet. This may cause risk of slips and falls.
- Protect from frost.

If further coatings will be applied later, **Chryso® Cure HPE must be removed** in accordance with technical guidelines.

### NORMATIVE AND REGULATORY INFORMATION

- CONF60

### SAFETY

The information contained in this document is given to the best of our knowledge and is the result of extensive and controlled testing. However, it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be conducted before the product is used to ensure that the methods and conditions of use of the product are satisfactory. Our specialists remain at the disposal of customers if they require help with the application of the product for their specific needs.

CHRYSO UK Ltd. - 1 Herald Way, Binley Industrial Estate, Coventry, United Kingdom, CV3

P.1/2

## TECHNICAL DATA SHEET

### Chryso® Cure HPE

Curing Agent  
Water based

Chryso  
Concrete  
Solutions

24/06/2026

For further information, please refer to the safety data sheet on our internet site [www.uk.chryso.com](http://www.uk.chryso.com).

The information contained in this document is given to the best of our knowledge and is the result of extensive and controlled testing. However, it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be conducted before the product is used to ensure that the methods and conditions of use of the product are satisfactory. Our specialists remain at the disposal of customers if they require help with the application of the product for their specific needs.

CHRYSO UK Ltd. - 1 Herald Way, Binley Industrial Estate, Coventry, United Kingdom, CV3

P.2/2